LOCAL DEVELOPMENT PLAN

'Ridgeview' Stage 9E Treendale

Application of Local Development Plan

This Local Development Plan (LDP) applies to Lots 99-108 and future lot 'A' Carnelian Avenue 'Ridgeview', Treendale as shown in the plan.

Residential Design Code

The Residential Design Coding for the subject lots as per the adopted Treendale Farm Structure Plan is 'R-20'.

Design Guidelines

The Treendale Estate Annexure 'A' Development Conditions and Building Guidelines are applicable to the subject lots.

Setbacks and Building Envelopes

Development setbacks to lot boundaries as per the Residential Design Codes are:

- a. Primary Street: Primary Building Envelope 3m. Development must comply with the R20 density provisions of the Residential Design Codes with primary street setbacks measured from the primary street boundary.
- b. Side boundaries: as per the Residential Design Codes Table 2a (walls with no major openings minimum is 1m setback for wall heights 3.5m or less and wall length 9m or less) and Table 2b (walls with major openings minimum is 1.5m setback for wall heights 3.5m or less and any wall length). The actual width of building envelopes is determined by Tables 2a and 2b.
- c. Rear boundary: Primary Building Envelope top of embankment as designated on the plan. Secondary Envelope 1.5m.

Primary Building Envelope

Dwellings, garages, carports and sheds must be located within the Primary Building Envelope.

Secondary Envelope

Upper Tier

- a. The maximum height of retaining for the Upper Tier is 1.5m above existing ground levels. This is to be constructed from reconstituted limestone blocks
- b. Incidental developments such as pools, spas, shade sails, pergolas, decking, paved areas and gardens in accordance with the Bushfire Management Plan may be constructed.
- c. No elevated decks (500mm or more above ground level) or sheds are to be constructed within the secondary envelope Upper Tier.
- d. Maximum wall height of incidental development shall not exceed 2.4m (measured from the primary building envelope ground FFL).
- e. Solid side fencing is not to exceed 1.8m in height and shall rake down to 1.2m in height (over 1.5m) to the Upper Tier's Rear fence. Rear fencing to the Upper Tier shall be open style (pool type fencing) 1.2m in height. All side and rear boundary fencing (Primary and Secondary Envelopes) to be consistent in colour.

Lower Tier/s

- a. The maximum height of retaining for the Lower Tier is 1.0m. This is to be constructed from reconstituted limestone blocks.
- b. Incidental developments such as paved areas and gardens in accordance with the Bushfire Management Plan may be constructed.
- c. No structures are to be constructed within the secondary envelope Lower Tier/s other than the abovementioned retaining.
- d. Solid fencing 1.2m in height is to be constructed to the side boundaries of lower tiers. Open side (pool type) fencing 1.2m in height is to be constructed to rear boundaries of the Lower Tier/s. All side and rear boundary fencing to be consistent in colour with the balance of fencing on the property.

Landscape planting

Landscape planting of the area between the rear boundary and the top of embankment is limited to low fuel vegetation to avoid increasing the risk of bushfire impact on the Primary Building Envelope.

Bushfire Attack Levels

- a. Bushfire Attack Level (BAL) construction standards for dwellings and any outbuilding located within 6m of the dwelling are to comply with a BAL assessment prepared by a suitably qualified persons.
- b. For lots 99-108, the BALs are identified in the plan. The highest BAL rating applies to the whole of the dwelling except where shielding provisions under Australian Standard AS3959 apply. More information on BALs can be found in the Bushfire Management Plan.

Approval

This LDP has been approved by the Shire of Harvey under Clause 52 of the *Planning and Development (Local Planning Schemes) Regulations* 2015.

Unsigned version Approved 10/10/2022 Valid until 11/09/2028
Signature Date

LEGEND Primary Building Envelope Secondary Envelope Uniform fencing Top of bank Dual use path 99 Bushfire Attack Level (BAL) 844m² BAL-29 100 720m² BAL-19 BAL-12.5 101 *Refer to Setbacks and Building Envelopes text 794m² 102 780m² 103 782m² 104 782m² 105 877m² 106 918m² 107 887m² Regional Open Space 108 894m² LOCATION MAP 826m² JBIECT LAND TREENDALE SOUTH DEVELOPMENT

LOCAL DEVELOPMENT PLAN

'RIDGEVIEW' TREENDALE



